

M A T E R I A L S A F E T Y D A T A S H E E T

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : DAP ORIGINAL CONTACT CEMENT - GELLED

UPC NUMBER : 25310, 25312, 25316

PRODUCT USE/CLASS : Contact Adhesive

MANUFACTURER

DAP INC

2400 BOSTON STREET

BALTIMORE, MD 21224

24 HOUR EMERGENCY:

TRANSPORTATION 1-800-535-5053 (352-323-3500)

MEDICAL 1-800-327-3874 (513-558-5111)

PREPARE DATE . 08/26/1996

GENERAL INFORMATION

REVISION NO. . 2

DAP INC. 1-888-DAP-TIPS (1-888-327-8477)

REVISION DATE 12/30/1999

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % RANGE
01	Toluene	108-88-3	45 0-50 0 %
02	Aliphatic Petroleum Distillate	64742-89-8	15 0-20 0 %
03	Methyl ethyl ketone	78-93-3	10 0-15.0 %

EXPOSURE LIMITS

ITEM	ACGIH		OSHA		COMPANY	
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	SKIN
01	50 ppm.	N.E	100 ppm	N E	N.E.	YES
02	400 ppm	N E	400 ppm	N E	N.E	NO
03	200 ppm	300 ppm	200 ppm	N E	N E	NO

(See Section 16 for abbreviation legend)

Remaining ingredients are not considered hazardous per the OSHA Hazard Communication Standard

Listed Permissible Exposure Levels (PEL) are from the U.S. Dept of Labor OSHA Final Rule Limits (CFR 29 1910 1000); limits may vary between states

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW. DANGER! Extremely flammable liquid and vapor. Vapor harmful Harmful or fatal if swallowed Vapors may cause flash fire or explosion. Aspiration hazard if swallowed - can enter lungs and cause

(Continued on Page 2)

SECTION 3 - HAZARDS IDENTIFICATION

damage. Harmful if inhaled

POTENTIAL HEALTH EFFECTS:

EFFECTS OF OVEREXPOSURE - EYE CONTACT May cause eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT May irritate skin Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - INHALATION Vapor harmful if inhaled. Vapor may irritate nose and upper respiratory tract Vapor inhalation may affect the brain or nervous system causing dizziness, headache or nausea

EFFECTS OF OVEREXPOSURE - INGESTION. This material may be harmful or fatal if swallowed. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal. If ingested, this product may cause vomiting, diarrhea, and depressed respiration.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS. Reports have associated permanent brain and nervous system damage with prolonged and repeated occupational overexposure to solvents. Overexposure or misuse of toluene can cause liver, kidney, and brain damage as well as cardiac abnormalities. Symptoms include loss of memory, loss of intellectual ability, and loss of coordination

MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY CONTACT: None known

PRIMARY ROUTE(S) OF ENTRY SKIN CONTACT INHALATION

SECTION 4 - FIRST AID MEASURES

EYE CONTACT Flush with large quantities of water until irritation subsides Contact a physician.

SKIN CONTACT Wash with soap and water.

INHALATION: Remove to fresh air If not breathing, give artificial respiration. If breathing is difficult, give oxygen Contact a physician immediately.

INGESTION. DO NOT INDUCE VOMITING. If irritation or complications arise, contact a physician or Regional Poison Control Center immediately

COMMENTS: None.

(Continued on Page 3)

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 21 F. minimum
(SETAFLASH CLOSED CUP)

LOWER EXPLOSIVE LIMIT. N.A.
UPPER EXPLOSIVE LIMIT: N A

AUTOIGNITION TEMPERATURE. N E.

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS Extremely flammable Material will readily ignite at room temperature. Vapors may form an explosive mixture with air Vapors can travel through a source of ignition and flashback Containers may explode if exposed to extreme heat Eliminate sources of ignition: heat, electrical equipment, sparks, and flames. Do not put in contact with oxidizing or caustic materials

SPECIAL FIREFIGHTING PROCEDURES: Full protective equipment, including self-contained breathing apparatus, is recommended to protect from combustion products. Cool exposed containers with water.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES. Dike spill area. Immediately eliminate sources of ignition. Use absorbent material or scrape up dried material and place into containers.

SECTION 7 - HANDLING AND STORAGE

HANDLING INFORMATION: KEEP OUT OF REACH OF CHILDREN Avoid skin and eye contact. Avoid breathing vapors. Use only in a well ventilated area

STORAGE INFORMATION Store away from caustics and oxidizers Keep away from heat, spark, and flame. Keep containers tightly closed when not in use Keep containers from excessive heat and freezing. Do not store at temperatures above 120 degrees F.

OTHER PRECAUTIONS. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal Do not take internally Construction and repair activities can adversely affect indoor air quality Consult with the occupants or a representative (i.e. maintenance, building manager, industrial hygienist, or safety officer) to determine ways to minimize any impact

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS Provide sufficient mechanical ventilation (local or general exhaust) to maintain exposure below PEL and TLV Vapors are

(Continued on Page 4)

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

heavier than air and will collect in low areas. Check all low areas (basements, sumps, etc) for vapors before entering

RESPIRATORY PROTECTION: If 8 hour exposure limit or value is exceeded for any component, use an approved NIOSH/OSHA respirator. Consult your safety equipment supplier and the OSHA regulation, 29 CFR 1910.134 for respirator requirements. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

EYE PROTECTION: Goggles or safety glasses with side shields.

SKIN PROTECTION: Solvent impervious gloves

OTHER PROTECTIVE EQUIPMENT: Provide eyewash and solvent impervious apron if body contact may occur

HYGIENIC PRACTICES: Remove contaminated clothing and wash before reuse

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE	: 170 - 180 F	VAPOR DENSITY	. Is heavier than air
ODOR	Hydrocarbon		
APPEARANCE	Tan Mobile Liquid	EVAPORATION RATE	Is faster than Butyl Acetate
SOLUBILITY IN H ₂ O	Negligible		
SPECIFIC GRAVITY	0.8903		
VAPOR PRESSURE	70 mm Hg @ 68F.		
PHYSICAL STATE	Liquid		

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Excessive heat and freezing

INCOMPATIBILITY: Strong oxidizers and caustics

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e. CO_x, NO_x

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions

STABILITY: This product is stable under normal storage conditions

SECTION 11 - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available

(Continued on Page 5)

SECTION 12 - ECOLOGICAL INFORMATION

No Information.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE MANAGEMENT/DISPOSAL· Dispose of according to Federal, State, and Local Standards. Discarded material should be incinerated at a permitted facility. Liquids cannot be disposed of in a landfill. Do not reuse empty container. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

EPA WASTE CODE - If discarded (40 CFR 261) D001-Ignitable

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Adhesive (Consumer Commodity*)

DOT HAZARD CLASS 3 (ORM-D*)

DOT UN/NA NUMBER· UN 1133 (NONE*) PACKING GROUP III (NONE*)

* For containers of 1 gallon or less

SECTION 15 - REGULATORY INFORMATION

U S FEDERAL REGULATIONS AS FOLLOWS -

OSHA Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372

CHEMICAL NAME	CAS NUMBER	WT/WT % RANGE
Toluene	108-88-3	45.0-50.0 %
Methyl ethyl ketone	78-93-3	10.0-15.0 %

TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

CHEMICAL NAME	CAS NUMBER
No information is available.	

(Continued on Page 6)

SECTION 15 - REGULATORY INFORMATION

NEW JERSEY RIGHT-TO-KNOW.

The following materials are non-hazardous, but are among the top five components in this product

----- CHEMICAL NAME -----	CAS NUMBER
Polychlorinated Rubber	TSRN-618608-5001P
Polychlorinated Rubber	TSRN-618608-5023P

PENNSYLVANIA RIGHT-TO-KNOW.

The following non-hazardous ingredients are present in the product at greater than 3%.

----- CHEMICAL NAME -----	CAS NUMBER
Polychlorinated Rubber	proprietary
Phenolic resin	proprietary

CALIFORNIA PROPOSITION 65.

WARNING. The chemical(s) noted below and contained in this product, are known to the state of California to cause birth defects or other reproductive harm.

----- CHEMICAL NAME -----	CAS NUMBER
Toluene	108-88-3

INTERNATIONAL REGULATIONS. AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS No information available

(Continued on Page 7)

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 2 FLAMMABILITY: 3 REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 02/01/1997

REASON FOR REVISION:

SECTION 1: Address change and new emergency contact phone numbers.

VOC less water, less exempt solvent: 690-700 gm/l(77-78%)

VOC material: 685-690 gm/l(76-77%)

LEGEND: ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS
N A. - NOT APPLICABLE
N.E. - NOT ESTABLISHED
PEL - PERMISSIBLE EXPOSURE LIMIT
NTP - NATIONAL TOXICOLOGY PROGRAM
SARA - SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986
STEL - SHORT TERM EXPOSURE LIMIT
TLV - THRESHOLD LIMIT VALUE(8 HR TIME WEIGHTED AVERAGE OR TWA)
VOC - VOLATILE ORGANIC COMPOUND
NJRTK - NEW JERSEY RIGHT TO KNOW LAW
N D. - NOT DETERMINED

MSDS# 30536

This data is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.

< End OF MSDS >